

Halder norm+technik



Design/Description:

Simplex mallet with cast iron housing and wooden handle

Inserts:

Plastic, red on both sides
hard


Field of application:

Automobile assembly and repair work, car body work, repair and maintenance work, sheet-metal working, dent removal, masonry work, scaffold construction



EH 3006.

Simplex mallet



Art. No.	Ø		—		—		g oz	
	mm	inch	mm	inch	mm	inch	g	oz
3006.030	30	1.18	90	3.54	300	11.81	345	12
3006.040	40	1.57	110	4.33	330	12.99	635	22
3006.050	50	1.96	135	5.32	350	13.78	1120	40
3006.060	60	2.36	145	5.71	405	15.95	1520	54

Design/Description:

Simplex mallet with cast iron housing and wooden handle

Inserts:

Superplastic, white on both sides
medium hard


Field of application:

Paving, curbstone setting, scaffold construction, tent and hall construction, gardening and landscaping, sheet-metal working, dent removal, automobile assembly and repair work, car body work, housing assembly, assembly of sharp-edged work pieces, fence construction, wood splitting with wedge, concrete form set-up



EH 3007.

Simplex mallet



Art. No.	Ø		—		—		g oz	
	mm	inch	mm	inch	mm	inch	g	oz
3007.030	30	1.18	90	3.54	300	11.81	320	11
3007.040	40	1.57	110	4.33	330	12.99	610	22
3007.050	50	1.96	135	5.32	350	13.78	1040	37
3007.060	60	2.36	145	5.71	405	15.95	1440	51
3007.080	80	3.14	175	6.89	490	19.27	2660	94

Design/Description:

Simplex mallet with cast iron housing and wooden handle

Inserts:

Nylon, white on both sides
hard


Field of application:

Scaffold construction, tent and hall construction, mould construction, automobile assembly and repair work, sheet-metal working, dent removal, housing assembly, assembly of sharp-edged work pieces, joining of work pieces, maintenance and repair work on agricultural machinery



EH 3008.

Simplex mallet



Art. No.	Ø		—		—		g oz	
	mm	inch	mm	inch	mm	inch	g	oz
3008.030	30	1.18	90	3.54	300	11.81	340	12
3008.040	40	1.57	110	4.33	330	12.99	650	23
3008.050	50	1.96	135	5.32	350	13.78	1130	40
3008.060	60	2.36	145	5.71	405	15.95	1500	53
3008.080	80	3.14	175	6.89	490	19.27	2880	102

* Inserts p.18 - 20, housings p.21, handles p.22, combination example p.15, fitting instruction p.23